



MODEL	Airflow Range	Horsepower Range	Weight (With filter elements)	Dimensions						Primary Element	Safety Element
				L	J	K	Ø A	Ø B	Ø C		
C 021	0.5 to 2.0 m ³ /min (18 to 71 CFM)	10 to 50 HP (8 to 38 KW)	1.90 kg (4.19 lbs)	322 mm (12.68")	55 mm (2.17")	97 mm (3.82")	9 mm (0.35")	40 mm (1.57")	157 mm (6.18")	E 021	-
C 031	1.0 to 3.5 m ³ /min (35 to 124 CFM)	20 to 70 HP (15 to 52 KW)	3.50 kg (7.70 lbs)	382 mm (15.04")	175 mm (6.89")	120 mm (4.72")	9 mm (0.35")	63 mm (2.5")	168 mm (6.61")	E 504	-
C 051	1.5 to 3.5 m ³ /min (53 to 124 CFM)	30 to 70 HP (22 to 52 KW)	3.90 kg (8.60 lbs)	382 mm (15.04")	175 mm (6.89")	120 mm (4.72")	9 mm (0.35")	63 mm (2.5")	188 mm (7.40")	E 504	-
C 071	3.5 to 4.5 m ³ /min (124 to 159 CFM)	50 to 70 HP (37 to 52 KW)	4.70 kg (10.35 lbs)	489 mm (19.25")	175 mm (6.89")	120 mm (4.72")	9 mm (0.35")	63 mm (2.5")	188 mm (7.40")	EP 070	ES 070
C 081	4.5 to 6.0 m ³ /min (159 to 212 CFM)	70 to 80 HP (52 to 60 KW)	5.75 kg (12.70 lbs)	520 mm (20.47")	175 mm (6.89")	120 mm (4.72")	9 mm (0.35")	70 mm (2.75")	204 mm (8.03")	EP 080	ES 080
C 121	6.0 to 8.0 m ³ /min (212 to 282 CFM)	80 to 110 HP (60 to 82 KW)	7.50 kg (16.50 lbs)	564 mm (22.20")	255 mm (10.04")	161 mm (6.34")	9 mm (0.35")	76 mm (3")	230 mm (9.06")	EP 120	ES 120
C 181	8.0 to 12.0 m ³ /min (282 to 423 CFM)	110 to 150 HP (82 to 112 KW)	9.20 kg (20.30 lbs)	616 mm (24.25")	255 mm (10.04")	161 mm (6.34")	9 mm (0.35")	102 mm (4")	254 mm (10")	EP 180	ES 180
C 221	12.0 to 15.0 m ³ /min (423 to 529 CFM)	150 to 180 HP (112 to 135 KW)	11.00 kg (24.20 lbs)	647 mm (25.47")	255 mm (10.04")	161 mm (6.34")	9 mm (0.35")	102 mm (4")	288 mm (11.34")	EP 220	ES 220
C 251	15.0 to 20.0 m ³ /min (529 to 706 CFM)	180 to 240 HP (134 to 179 KW)	13.60 kg (30.00 lbs)	714 mm (28.11")	-	140 mm (5.51")	10 mm (0.39")	133 mm (5.25")	337 mm (13.27")	EP 250	ES 250
C 261	20.0 to 21.0 m ³ /min (706 to 741 CFM)	200 to 260 HP (149 to 194 KW)	14.50 kg (31.90 lbs)	780 mm (30.71")	-	140 mm (5.51")	10 mm (0.39")	130 mm (5.12")	337 mm (13.27")	EP 260	ES 260
C 311	21.0 to 28.0 m ³ /min (741 to 988 CFM)	260 to 320 HP (194 to 239 KW)	16.70 kg (36.80 lbs)	785 mm (30.90")	-	200 mm (7.87")	10 mm (0.39")	152 mm (6")	373 mm (14.69")	EP 310/P	ES 310/P
C 351	28.0 to 35.0 m ³ /min (988 to 1235 CFM)	320 to 380 HP (239 to 283 KW)	21.00 kg (46.25 lbs)	800 mm (31.50")	-	200 mm (7.87")	10 mm (0.39")	152 mm (6")	420 mm (16.53")	EP 350	ES 350
C 431	35.0 to 43.0 m ³ /min (1235 to 1517 CFM)	380 to 450 HP (283 to 335 KW)	29.00 kg (63.90 lbs)	971 mm (38.23")	-	200 mm (7.87")	10 mm (0.39")	152 mm (6")	478 mm (18.82")	EP 430	ES 430

Oblan s.a. has the right to modify the information contained in this brochure without its previous advise.

- Notes:
- 1) In normally aspirated engines the model selection by horsepower range is just a recommendation.
 - 2) In turbocharged or turbo-aftercooled engines the correct model selection is based on the maximum air flow.
 - 3) For particular applications you have a complete line of installation accessories.